

PRO SERIES

REPLACEMENT WINDOWS



200 SLIDING WINDOW



BUILT TO LAST. MADE TO IMPRESS.

You have a vision for how you want your replacement windows to look. Ply Gem Windows Pro Series can help you realize that vision. Every window is designed to fit your needs. You'll find the right sizes, the right designs and the right solutions to help make your window replacement project a success.



NEW!
DUAL WALL
FLUSH FIN



200 SLIDING WINDOW



PLY GEM PRO SERIES 200 WINDOWS HAVE BEEN GREEN APPROVED BY THE NAHB RESEARCH CENTER.

This means you can be assured that Ply Gem Pro Series 200 windows comply with specific green practice criteria in the National Green Building Standard. Visit www.GreenApprovedProducts.com for more details.

THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
WITH WARM EDGE				
3/4" Clear	2.04	0.49	0.60	0.64
3/4" HP	3.13	0.32	0.29	0.54
3/4" HP ^{SC}	3.13	0.32	0.22	0.43
WITH WARM EDGE+				
3/4" HP	3.33	0.30	0.29	0.54
3/4" HP ^{SC}	3.33	0.30	0.22	0.43

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

STANDARD FEATURES

- Dual wall flush fin for enhanced strength and enduring beauty
- Low-point, high-pressure weep system helps water drain efficiently from frame
- Wide brass adjustable rollers for smooth operation
- Limited sash stop and removable sash
- Continuous weatherstripping and dual cam-action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient warm edge insulating glass for enhanced energy performance
- Corrosion-resistant stainless steel screws and hardware for lifelong durability
- Aluminum-reinforced meeting rail for added strength and durability
- Maintenance-free multi-chamber PVC construction with fusion welded corners for durability, weather-tight performance and beauty
- 3 7/16" frame depth with heavy vinyl walls for strength and stability
- Rated for light commercial application



OPTIONS

GLASS OPTIONS:

HP glass, HP^{SC} glass, Warm Edge+, STC options, tints, obscure, laminated, tempered, single glaze



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulated-divided-lite (SDL) 7/8" or 1 1/4" styles; 2" accent bar



HARDWARE OPTIONS:

AUTOLOCK—positive action lock

FRAME OPTIONS:

Dual wall flush fin, no fin, 1" or 1 3/8" nail fin setback with stucco key or J-channel; Insulair passive fresh air ventilation system



COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Most units rated DP25 standard.
2. Low-E with argon.
3. Optional Solar Cooling optimized Low-E with argon.
4. Optional Sound Control.
5. Optional Warm Edge+ spacer upgrade for enhanced performance.

NOTE: Optional 1" IGU for 1" sculptured GBG and some Sound Control Glass packages.

